

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11-Aug-2015

Print date: 28-Aug-2015

Version: 1.0

Page 1/9



## FOKALDRY

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name/designation:

FOKALDRY

Article No.:

0032305 (80 ml), 0032306 (500 ml)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Medical device for dental application. Observe instructions for use.

For professional use only,

#### 1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

lege artis Pharma GmbH + Co. KG

Breitwasenring 1

72135 Dettenhausen

GERMANY

Telephone: +49 (0) 71 57 / 56 45 - 0

Telefax: +49 (0) 71 57 / 56 45 - 50

E-mail: info@legeartis.de

Website: www.legeartis.de

E-mail (competent person): sicherheitsdatenblaetter@legeartis.de

#### 1.4. Emergency telephone number

24h: +49 (0) 551 / 192 40, +49 (0) 71 57 / 56 45 - 0 (Only available during office hours.)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Serious eye damage/eye irritation ( <i>Eye Irrit. 2</i> )	H319: Causes serious eye irritation.	
flammable liquids ( <i>Flam. Liq. 2</i> )	H225: Highly flammable liquid and vapour.	
Aspiration hazard ( <i>Asp. Tox. 1</i> )	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation ( <i>Skin Irrit. 2</i> )	H315: Causes skin irritation.	
STOT-single exposure ( <i>STOT SE 3</i> )	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment ( <i>Aquatic Chronic 3</i> )	H412: Harmful to aquatic life with long lasting effects.	

#### Additional information:

Contains: Isopropyl ether, Solvent (C6-C7), Acetone, Isopropanol

May form explosive peroxides. Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye

protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER. IF ON SKIN: Gently wash

with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/

attention.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11-Aug-2015

Print date: 28-Aug-2015

Version: 1.0

Page 2/9



## FOKALDRY

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

According to EC directives or the corresponding national regulations the product does not have to be labelled.

#### Additional information:

As a medical device this product is not subject to Regulation (EC) no. 1272/2008 [CLP] and do not require labeling according this regulation.

### 2.3. Other hazards

#### Adverse human health effects and symptoms:

Special danger of slipping by leaking/spilling product.

## SECTION 3: Composition / information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No. 1272/2008 [CLP]	Concentration
CAS No.: 108-20-3 EC No.: 203-560-6	Isopropyl ether STOT SE 3, Flam. Liq. 2 <b>Danger</b> H225-H336-EUH019-EUH066	40 - 60 Wt %
CAS No.: 67-64-1 EC No.: 200-662-2	Acetone STOT SE 3, Flam. Liq. 2, Eye Irrit. 2 <b>Danger</b> H225-H319-H336-EUH066	10 - 20 Wt %
CAS No.: 67-63-0 EC No.: 200-661-7	Propan-2-ol STOT SE 3, Flam. Liq. 2, Eye Irrit. 2 <b>Danger</b> H225-H319-H336	10 - 20 Wt %
CAS No.: 64742-49-0 EC No.: 265-151-9 INDEX No.: 649-328-00-1	Naphtha (petroleum), hydrotreated light STOT SE 3, Flam. Liq. 2, Skin Irrit. 2, Asp. Tox. 1, Aquatic Chronic 2 <b>Danger</b> H225-H304-H315-H336	10 - 20 Wt %
CAS No.: 109-66-0 EC No.: 203-692-4	Pentane STOT SE 3, Flam. Liq. 2, Asp. Tox. 1, Aquatic Chronic 2 <b>Danger</b> H225-H304-H336-H411-EUH066	5 - 15 Wt %

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing. If unconscious place in recovery position and seek medical advice. Do not leave affected person unattended.

#### Following inhalation:

Provide fresh air. Get medical advice/attention if you feel unwell.

#### In case of skin contact:

Gently wash with plenty of soap and water. In case of skin irritation, consult a physician.

#### After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### After ingestion:

Rinse mouth. Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

**Revision date:** 11-Aug-2015

**Print date:** 28-Aug-2015

**Version:** 1.0

Page 3/9



## FOKALDRY

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media:

Water spray jet, alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO<sub>2</sub>).

### 5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour. The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration. Beware of reignition.

#### Hazardous combustion products:

In case of fire may be liberated: Gases/vapours, toxic

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

### 5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

##### Personal precautions:

Do not breathe gas/vapour/aerosol. Avoid contact with eyes and skin. Special danger of slipping by leaking/spilling product. Remove persons to safety.

##### Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

#### 6.1.2. For emergency responders

##### Personal protection equipment:

Personal protection equipment: see section 8

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

#### For containment:

Wipe up with absorbent material (eg. cloth, fleece). Handling larger quantities: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up:

Water (with cleaning agent)

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### 6.5. Additional information

Use appropriate container to avoid environmental contamination.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Protective measures

##### Advices on safe handling:

Do not breathe gas/vapour/aerosol. Avoid contact with eyes and skin. Take off immediately all contaminated clothing. Wear personal protection equipment (refer to section 8).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

**Revision date:** 11-Aug-2015

**Print date:** 28-Aug-2015

**Version:** 1.0

Page 4/9



## FOKALDRY

### Fire prevent measures:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep cool. Protect from sunlight.

### Environmental precautions:

Discharge into the environment must be avoided.

### Advices on general occupational hygiene

When using do not eat, drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Apply skin care products after work.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Protect from sunlight.

Recommended storage temperature: 15 - 25 °C

#### Requirements for storage rooms and vessels:

Floors should be impervious, resistant to liquids and easy to clean. Keep/Store only in original container.

#### Hints on storage assembly:

Keep away from food, drink and animal feedingstuffs.

**Storage class:** 3 - Flammable liquids

### 7.3. Specific end use(s)

#### Recommendation:

Medical device for dental application.

Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control Parameters

#### 8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
WEL (GB)	Isopropyl ether CAS No.: 108-20-3	① 250 ppm (1,060 mg/m <sup>3</sup> ) ② 310 ppm (1,310 mg/m <sup>3</sup> )
WEL (GB)	Acetone CAS No.: 67-64-1	① 500 ppm (1,210 mg/m <sup>3</sup> ) ② 1,500 ppm (3,620 mg/m <sup>3</sup> )
IOELV (EU)	Acetone CAS No.: 67-64-1	① 500 ppm (1,210 mg/m <sup>3</sup> )
WEL (GB)	Propan-2-ol CAS No.: 67-63-0	① 400 ppm (999 mg/m <sup>3</sup> ) ② 500 ppm (1,250 mg/m <sup>3</sup> )
GB	Naphtha (petroleum), hydrotr eated light CAS No.: 64742-49-0	① 1,800 mg/m <sup>3</sup> ⑤ (C5-C6 alkenes)
WEL (GB)	Pentane CAS No.: 109-66-0	① 600 ppm (1,800 mg/m <sup>3</sup> )
IOELV (EU)	Pentane CAS No.: 109-66-0	① 1,000 ppm (3,000 mg/m <sup>3</sup> )

#### 8.1.2. Biological limit values

No data available

#### 8.1.3. DNEL-/PNEC-values

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11-Aug-2015

Print date: 28-Aug-2015

Version: 1.0

Page 5/9



## FOKALDRY

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

#### 8.2.2. Personal protection equipment



##### Eye/face protection:

Eye glasses with side protection (DIN EN 166).

##### Skin protection:

Tested protective gloves must be worn (DIN EN 374).

Suitable material: IIR (butyl rubber)

Thickness of the glove material:  $\geq 0,7$  mm

Breakthrough time (maximum wearing time):  $\geq 480$  min

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. The exact break trough time has to be obtained from the protective glove manufacturer and must be observed. Check leak tightness/ impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well.

##### Respiratory protection:

Usually no personal respirative protection necessary. Provide adequate ventilation.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device (full mask or mouthpiece) with filter: AX

##### Other protection measures:

Wear suitable protective clothing.

#### 8.2.3. Environmental exposure controls

No data available

### 8.3. Additional information

No data available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state: liquid

Colour: colourless

Odour: like Isopropyl ether

#### Safety relevant basis data

Parameter		at °C	Method	Remark
pH	<i>not applicable</i>			
Melting point/freezing point	<i>not determined</i>			
Freezing point	<i>not determined</i>			
Initial boiling point and boiling range	$\geq 44$ °C			
Decomposition temperature (°C):	<i>not determined</i>			
Flash point	$\approx -10 - 0$ °C			(estimated)
Evaporation rate	<i>not determined</i>			
Ignition temperature in °C	$\geq 280$ °C			
Upper/lower flammability or explosive limits	1 - 21 Vol-%			(Isopropyl ether)
Vapour pressure	<i>not determined</i>			
Vapour density	<i>not determined</i>			
Density	0.7 g/ml	20 °C		
Bulk density	<i>not applicable</i>			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

**Revision date:** 11-Aug-2015

**Print date:** 28-Aug-2015

**Version:** 1.0

Page 6/9



## FOKALDRY

Parameter		at °C	Method	Remark
Water solubility (g/L)	insoluble			
Partition coefficient: n-octanol/ water	<i>not determined</i>			
Dynamic viscosity	<i>not determined</i>			
Kinematic viscosity	<i>not determined</i>			

### 9.2. Other information

No data available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

Exothermic reaction with: Amines; Acids; Oxidising agent, strong

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep cool. Protect from sunlight.

### 10.5. Incompatible materials

Amines; Acids; Oxidising agent, strong; plastic

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Gases/vapours, toxic

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

CAS No.	Substance name	Toxicological information
109-66-0	Pentane	<b>LD<sub>50</sub> oral:</b> 400 mg/kg (Rat)

#### Acute oral toxicity:

Based on available data, the classification criteria are not met.

#### Acute dermal toxicity:

Based on available data, the classification criteria are not met.

#### Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation:

Causes skin irritation.

#### Eye damage/irritation:

Causes serious eye irritation.

#### Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

#### Carcinogenicity:

Based on available data, the classification criteria are not met.

#### Reproductive toxicity:

Based on available data, the classification criteria are not met.

#### STOT-single exposure:

Vapours may cause drowsiness and dizziness.

#### STOT-repeated exposure:

Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

**Revision date:** 11-Aug-2015

**Print date:** 28-Aug-2015

**Version:** 1.0

Page 7/9



## FOKALDRY

### Aspiration hazard:

May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Aquatic toxicity:

Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

#### Biodegradation:

There are no data available on the preparation/mixture itself. Some of the components are poorly biodegradable.

### 12.3. Bioaccumulative potential

#### Accumulation / Evaluation:

No indication of bioaccumulation potential.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

No data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Waste treatment options

##### Appropriate disposal / Product:

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

##### Appropriate disposal / Package:

Completely emptied packages can be recycled.





##### Other disposal recommendations:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Collect in closed and suitable containers for disposal.

### 13.2. Additional information

Waste for disposal is to be classified and labelled.

## SECTION 14: Transport information

Land transport (ADR / RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO- TI / IATA-DGR)
<b>14.1. UN-No.</b>			
1993	1993	1993	1993
<b>14.2. UN proper shipping name</b>			
FLAMMABLE LIQUID, N.O.S. (DIISOPROPYL E- THER, ACETONE)	FLAMMABLE LIQUID, N.O.S. (DIISOPROPYL E- THER, ACETONE)	FLAMMABLE LIQUID, N.O.S. (DIISOPROPYL E- THER, ACETONE)	FLAMMABLE LIQUID, N.O.S. (DIISOPROPYL E- THER, ACETONE)
<b>14.3. Transport hazard class(es)</b>			
 3	 3	 3	 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11-Aug-2015

Print date: 28-Aug-2015

Version: 1.0

Page 8/9



## FOKALDRY

Land transport (ADR / RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
<b>14.4. Packing group</b>			
II	II	II	II
<b>14.5. Environmental hazards</b>			
No	No	No	No
<b>14.6. Special precautions for user</b>			
<b>Special provisions:</b> 274, 601, 640C <b>Limited quantity (LQ):</b> 1 L <b>Hazard identification number (Kemler No.):</b> 33 <b>Classification code:</b> F1 <b>Tunnel restriction code:</b> D/E <b>Remark:</b> -	<b>Special provisions:</b> not determined <b>Limited quantity (LQ):</b> not determined <b>Classification code:</b> F1 <b>Remark:</b> -	<b>Special provisions:</b> not determined <b>Limited quantity (LQ):</b> not determined <b>EmS-No.:</b> F-E; S-D <b>Remark:</b> -	<b>Special provisions:</b> not determined <b>Limited quantity (LQ):</b> not determined <b>Remark:</b> -

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

#### Additional information:

Small amounts: Transport as "limited quantity" according to chapter 3.4 ADR/RID / Transport as "excepted quantity" according to chapter 3.5 ADR/RID,

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU legislation

##### Other regulations (EU):

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Directive 93/42/EEC concerning medical devices.

#### 15.1.2. National regulations

No data available

### 15.2. Chemical Safety Assessment

No data available.

### 15.3. Additional information

No data available.

## SECTION 16: Other information

### 16.1. Indication of changes

No data available.

### 16.2. Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

**Revision date:** 11-Aug-2015

**Print date:** 28-Aug-2015

**Version:** 1.0

Page 9/9



## FOKALDRY

### 16.3. Key literature references and sources for data

No data available.

### 16.4. Classification for mixtures and used evaluation method according to regulation (EC) No. 1272/2008 [CLP]

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Serious eye damage/eye irritation ( <i>Eye Irrit. 2</i> )	H319: Causes serious eye irritation.	
flammable liquids ( <i>Flam. Liq. 2</i> )	H225: Highly flammable liquid and vapour.	
Aspiration hazard ( <i>Asp. Tox. 1</i> )	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation ( <i>Skin Irrit. 2</i> )	H315: Causes skin irritation.	
STOT-single exposure ( <i>STOT SE 3</i> )	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment ( <i>Aquatic Chronic 3</i> )	H412: Harmful to aquatic life with long lasting effects.	

### 16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

### 16.6. Training advice

No data available.

### 16.7. Additional information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.